



*live inspired*

# ARTE

COLOR BODY PORCELAIN TILE | RECTIFIED



**AJ3P** Arte BI  
20"x20" Rectified  
**AJ3L** Arte BI  
13"x13" Rectified  
**AJ3S** Arte BI  
12"x24" Rectified  
**AJ3V** Arte BI  
3 1/4"x6 1/2" Rectified

**AJ3N** Arte BG  
20"x20" Rectified  
**AJ3K** Arte BG  
13"x13" Rectified  
**AJ3R** Arte BG  
12"x24" Rectified  
**AJ3U** Arte BG  
3 1/4"x6 1/2" Rectified


**AJ3Q** Arte MA  
20"x20" Rectified  
**AJ3M** Arte MA  
13"x13" Rectified  
**AJ3T** Arte MA  
12"x24" Rectified  
**AJ3W** Arte MA  
3 1/4"x6 1/2" Rectified



**AJ3Y** Arte BI  
Brick Mosaic  
13"x13"



**AJ3X** Arte BG  
Brick Mosaic  
13"x13"



**AJ3Z** Arte MA  
Brick Mosaic  
13"x13"

**TRIMS**



**AJ33** Arte BI Bullnose  
**AJ32** Arte BG Bullnose  
**AJ34** Arte MA Bullnose  
3"x13"

-  Floor Tile
-  Wall Tile
-  Rectified Tile
-  Suitable for Outdoors
-  Trim Available
-  Suitable for Outdoors
-  Moderate Variation
-  Frost Resistant
-  Meets ADA Recommendations
-  Abrasion Resistance
-  C.O.F. (Wet)
-  C.O.F. (Dry)
-  Certified No VOC
-  21% Minimum Pre-Consumer Recycled Content



Contributes to LEED Credits

## TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD	
Water Absorption	≤ 0.50%	≤ 0.50%	C373	
Frost Resistance	As Reported	Resistant	C1026	
Scratch Resistance	MOHS 1-10	6	MOHS SCALE	
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 605 lbf.	C648
	13"x13"	≥ 250 lbf.	≥ 407 lbf.	C648
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499	
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499	
Wedging (Squareness)	+/- 0.25 % or +/- 0.8 mm*	Within Standard	C502	
Warpage (Flatness)	+/- 0.40 % or +/- 1.8 mm*	Within Standard	C485	
Abrasion Resistance	Class 0 - Class V	Class IV	C1027	
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028	
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028	
Chemical Resistance	Class A - Class E	Class A	C650	
Stain Resistance	Class A - Class E	Class A	C1378	

\* Whichever is less

