



*live inspired*

# BOARDWALK

COLOR BODY PORCELAIN TILE

-  Floor Tile
-  Wall Tile
-  Decorative Tile
-  Trim Available
-  Suitable for Outdoors
-  Substantial Variation
-  Frost Resistant
-  Meets ADA Recommendations
-  Abrasion Resistance
-  C.O.F. (Wet)
-  C.O.F. (Dry)
-  21% Minimum Pre-Consumer Recycled Content
-  Certified No VOC



**AJ38** Boardwalk BG  
13"x13"



**AJ39** Boardwalk GR  
13"x13"



**AJ4A** Boardwalk MC  
13"x13"



**AJ4B** Boardwalk BG  
20"x20"



**AJ4Y** Boardwalk BG  
3 1/4"x6 1/2"



**AJ4C** Boardwalk GR  
20"x20"



**AJ4Z** Boardwalk GR  
3 1/4"x6 1/2"



**AJ4D** Boardwalk MC  
20"x20"



**AJ52** Boardwalk MC  
3 1/4"x6 1/2"



**AJ4L** Boardwalk BG Bullnose  
**AJ4M** Boardwalk GR Bullnose  
**AJ4N** Boardwalk MC Bullnose  
3"x13"

## TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD	
Water Absorption	≤ 0.50%	≤ 0.50%	C373	
Frost Resistance	As Reported	Resistant	C1026	
Scratch Resistance	MOHS 1-10	7	MOHS SCALE	
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 598 lbf.	C648
	13"x13"	≥ 250 lbf.	≥ 414 lbf.	C648
Facial Dimension	-3.0 % < Nominal ≤ 3.0 %	Within Standard	C499	
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499	
Wedging (Squareness)	+/- 0.50% or +/- 2.0 mm*	Within Standard	C502	
Warpage (Flatness)	+/- 0.75% or +/- 2.3 mm*	Within Standard	C485	
Abrasion Resistance	Class 0 - Class V	Class IV	C1027	
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028	
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028	
Chemical Resistance	Class A - Class E	Class A	C650	
Stain Resistance	Class A - Class E	Class A	C1378	

\* Whichever is less



Contributes to  
LEED Credits