

RAGNO  USA

BOARDWALK GLAZED PORCELAIN TILE | MADE IN THE USA



live inspired





live inspired

BOARDWALK

GLAZED PORCELAIN TILE | MADE IN THE USA



AJ38 Boardwalk BG
13"x13"



AJ39 Boardwalk GR
13"x13"



AJ4A Boardwalk MC
13"x13"

AJ4B Boardwalk BG
20"x20"

AJ4Y Boardwalk BG
3 1/4"x6 1/2"

AJ4C Boardwalk GR
20"x20"

AJ4Z Boardwalk GR
3 1/4"x6 1/2"

AJ4D Boardwalk MC
20"x20"

AJ52 Boardwalk MC
3 1/4"x6 1/2"



AJ53 Boardwalk BG
Mosaic - Square 2"x2"
13"x13"



AJ56 Boardwalk BG
Mosaic - Brick 1"x4 1/4"
13"x13"



AJ54 Boardwalk GR
Mosaic - Square 2"x2"
13"x13"



AJ57 Boardwalk GR
Mosaic - Brick 1"x4 1/4"
13"x13"



AJ55 Boardwalk MC
Mosaic - Square 2"x2"
13"x13"



AJ58 Boardwalk MC
Mosaic - Brick 1"x4 1/4"
13"x13"

TRIMS



AJ4L Boardwalk BG Bullnose

AJ4M Boardwalk GR Bullnose

AJ4N Boardwalk MC Bullnose

3"x13"



Floor Tile



Wall Tile



Decorative Tile



Trim Available



Suitable for Outdoors



Substantial Variation



Frost Resistant



Meets ADA Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



21% Minimum Pre-Consumer Recycled Content



Certified No VOC



Contributes to LEED Credits

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS SCALE
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 598 lbf.
	13"x13"	≥ 250 lbf.	≥ 414 lbf.
Facial Dimension	-3.0 % < Nominal ≤ 3.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50% or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75% or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Whichever is less

