

live inspired



BORGOFORTE

GLAZED PORCELAIN TILE



AG2H Siena GR
18"x18"
AG2D Siena GR
12"x12"




AG3P Siena GR Listelli
1 1/2"x12"



AG3T Siena GR Insert
1 1/2"x1 1/2"



AG2E Cassino BG
18"x18"
AG2A Cassino BG
12"x12"



AG2N Cassino BG Listelli
1 1/2"x12"



AG3Q Cassino BG Insert
1 1/2"x1 1/2"



AG2F Orvieto BL
18"x18"
AG2B Orvieto BL
12"x12"




AG3M Orvieto BL Listelli
1 1/2"x12"



AG3R Orvieto BL Insert
1 1/2"x1 1/2"



AG2G Perugia MA
18"x18"
AG2C Perugia MA
12"x12"



AG3N Perugia MA Listelli
1 1/2"x12"



AG3S Perugia MA Insert
1 1/2"x1 1/2"

TRIMS



AG2M Siena GR Bullnose
AG2K Orvieto BL Bullnose
AG2J Cassino BG Bullnose
AG2L Perugia MA Bullnose
3"x12"



Floor Tile



Wall Tile



Decorative Tile



Trim Available



Suitable for
Outdoors



Slight Variation



Frost Resistant



Meets ADA
Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



Certified No VOC



7% Minimum
Pre-Consumer
Recycled Content



Contributes to
LEED Credits

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS SCALE
Breaking Strength	18"x18" ≥ 250 lbf.	≥ 550 lbf.	C648
	12"x12" ≥ 250 lbf.	≥ 480 lbf.	C648
Facial Dimension	-3.0 % < Nominal ≤ 3.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Whichever is less

