

RAGNO  USA

BURGUNDY GLAZED PORCELAIN TILE | MADE IN THE USA



BURGUNDY

live inspired



live inspired



BURGUNDY

GLAZED PORCELAIN TILE | MADE IN THE USA



AF3N Burgundy GR
20"x20"
AF3J Burgundy GR
13"x13"
AF56 Burgundy GR
6 1/2"x6 1/2"



AG58 Burgundy GR
Mosaic - Square 2"x2"
13"x13"



AF3P Burgundy GO
20"x20"
AF3K Burgundy GO
13"x13"
AF57 Burgundy GO
6 1/2"x6 1/2"



AG59 Burgundy GO
Mosaic - Square 2"x2"
13"x13"

AF62 Burgundy GR Listelli
1"x13"

AF67 Burgundy Corner-Insert
1"x1"

AF63 Burgundy GO Listelli
1"x13"

AF67 Burgundy Corner-Insert
1"x1"




AF3Q Burgundy NO
20"x20"
AF3L Burgundy NO
13"x13"
AF58 Burgundy NO
6 1/2"x6 1/2"



AG6A Burgundy NO
Mosaic - Square 2"x2"
13"x13"



AF3R Burgundy TC
20"x20"
AF3M Burgundy TC
13"x13"
AF59 Burgundy TC
6 1/2"x6 1/2"



AG6B Burgundy TC
Mosaic - Square 2"x2"
13"x13"

AF64 Burgundy NO Listelli
1"x13"

AF67 Burgundy Corner-Insert
1"x1"

AF65 Burgundy TC Listelli
1"x13"

AF67 Burgundy Corner-Insert
1"x1"

TRIMS



AF35 Burgundy GR Bullnose
AF3T Burgundy GO Bullnose
AF3U Burgundy NO Bullnose
AF3V Burgundy TC Bullnose
3"x13"



AF5E Burgundy GR Bead
AF5F Burgundy GO Bead
AF5G Burgundy NO Bead
AF5H Burgundy TC Bead
1"x6 1/2"



AF5J Burgundy GR Beak
AF5K Burgundy GO Beak
AF5L Burgundy NO Beak
AF5M Burgundy TC Beak
1"x1"



AF5N Burgundy GR V-Cap
AF5P Burgundy GO V-Cap
AF5Q Burgundy NO V-Cap
AF5R Burgundy TC V-Cap
2"x6 1/2"



AF5S Burgundy GR V-Cap Corner
AF5T Burgundy GO V-Cap Corner
AF5U Burgundy NO V-Cap Corner
AF5V Burgundy TC V-Cap Corner
7/8"x2"

- Floor Tile
- Wall Tile
- Modular Tile
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- Moderate Variation
- Frost Resistant
- Meets ADA Recommendations
- Abrasion Resistance
- C.O.F. (Wet)
- C.O.F. (Dry)
- Certified No VOC
- 21% Minimum Pre-Consumer Recycled Content



Contributes to LEED Credits

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD	
Water Absorption	≤ 0.50%	≤ 0.50%	C373	
Frost Resistance	As Reported	Resistant	C1026	
Scratch Resistance	MOHS 1-10	6	MOHS SCALE	
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 530 lbf.	C648
	13"x13"	≥ 250 lbf.	≥ 400 lbf.	C648
Facial Dimension	-3.0 % < Nominal ≤ 3.0 %	Within Standard	C499	
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499	
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502	
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485	
Abrasion Resistance	Class 0 - Class V	Class IV	C1027	
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028	
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028	
Chemical Resistance	Class A - Class E	Class A	C650	
Stain Resistance	Class A - Class E	Class A	C1378	

* Whichever is less



AK65 Burgundy GR Cove Base
AK66 Burgundy GO Cove Base
AK67 Burgundy NO Cove Base
AK68 Burgundy TC Cove Base
6"x13"



AK69 Burgundy GR Cove Base In Angle
AK72 Burgundy GO Cove Base In Angle
AK73 Burgundy NO Cove Base In Angle
AK74 Burgundy TC Cove Base In Angle
1"x6"



AK75 Burgundy GR Cove Base Out Angle
AK76 Burgundy GO Cove Base Out Angle
AK77 Burgundy NO Cove Base Out Angle
AK78 Burgundy TC Cove Base Out Angle
1"x6"