

live inspired



# CLEFTSTONE

GLAZED PORCELAIN TILE



**92D1** Cleftstone BI  
20"x20"  
**91S1** Cleftstone BI  
13"x13"  
**91T5** Cleftstone BI  
6 1/2"x6 1/2"



**92D0** Cleftstone BG  
20"x20"  
**91S0** Cleftstone BG  
13"x13"  
**91T4** Cleftstone BG  
6 1/2"x6 1/2"



**92C8** Cleftstone GI  
20"x20"  
**91R8** Cleftstone GI  
13"x13"  
**91T2** Cleftstone GI  
6 1/2"x6 1/2"



**92C7** Cleftstone MT  
20"x20"  
**91R7** Cleftstone MT  
13"x13"  
**91T1** Cleftstone MT  
6 1/2"x6 1/2"



**92C6** Cleftstone VE  
20"x20"  
**91R6** Cleftstone VE  
13"x13"  
**91T0** Cleftstone VE  
6 1/2"x6 1/2"



**92C5** Cleftstone NE  
20"x20"  
**91R5** Cleftstone NE  
13"x13"  
**91S9** Cleftstone NE  
6 1/2"x6 1/2"



**AJ4T** Cleftstone MT  
Mosaic - Square 2"x2"  
13"x13"



**AJ4U** Cleftstone VE  
Mosaic - Square 2"x2"  
13"x13"



**AJ4V** Cleftstone NE  
Mosaic - Square 2"x2"  
13"x13"



**9127** Riverstone RED  
Freccia  
6 1/2"x13"



**9126** Riverstone GREEN  
Freccia  
6 1/2"x13"



**9129** Riverstone RED  
Freccia Corner  
6 1/2"x6 1/2"



**9128** Riverstone GREEN  
Freccia Corner  
6 1/2"x6 1/2"

## TRIMS



**93M9** Stone BI V-Cap Corner  
**93M8** Stone BG V-Cap Corner  
**93M7** Stone GI V-Cap Corner  
**93M6** Stone MT V-Cap Corner  
**93M5** Stone VE V-Cap Corner  
**93M4** Stone NE V-Cap Corner  
1 3/4"x2 1/4"



**93N5** Stone BI V-Cap  
**93N4** Stone BG V-Cap  
**93N3** Stone GI V-Cap  
**93N2** Stone MT V-Cap  
**93N1** Stone VE V-Cap  
**93N0** Stone NE V-Cap  
2 1/4"x13"



**91S8** Stone BI Bullnose  
**91S7** Stone BG Bullnose  
**91S5** Stone GI Bullnose  
**91S4** Stone MT Bullnose  
**91S3** Stone VE Bullnose  
**91S2** Stone NE Bullnose  
3"x13"



Floor Tile



Wall Tile



Modular Tile



Decorative Tile



Trim Available



Suitable for Outdoors



Moderate Variation



Frost Resistant



Meets ADA Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)  
21% Minimum Pre-Consumer Recycled Content



Certified No VOC



Contributes to LEED Credits

## TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD	
Water Absorption	≤ 0.50%	≤ 0.50%	C373	
Frost Resistance	As Reported	Resistant	C1026	
Scratch Resistance	MOHS 1-10	7	MOHS SCALE	
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 605 lbf.	C648
	13"x13"	≥ 250 lbf.	≥ 635 lbf.	C648
Facial Dimension	-3.0 % < Nominal ≤ 3.0 %	Within Standard	C499	
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499	
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502	
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485	
Abrasion Resistance	Class 0 - Class V	Class IV	C1027	
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028	
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028	
Chemical Resistance	Class A - Class E	Class A	C650	
Stain Resistance	Class A - Class E	Class A	C1378	

\* Whichever is less

