



*live inspired*

# ETERNAL LIMESTONES

COLOR BODY PORCELAIN TILE | RECTIFIED | 3D PRINTING TECHNIQUE



**Limestone AN**  
**AL2F** 3¼"x6½" Rectified  
**AL2C** 6"x24" Rectified  
**AL23** 12"x24" Rectified  
**AL29** 13"x13" Rectified  
**AL26** 20"x20" Rectified




**Limestone BG**  
**AL2G** 3¼"x6½" Rectified  
**AL2D** 6"x24" Rectified  
**AL24** 12"x24" Rectified  
**AL2A** 13"x13" Rectified  
**AL27** 20"x20" Rectified



**Limestone BI**  
**AL2E** 3¼"x6½" Rectified  
**AL2B** 6"x24" Rectified  
**AL22** 12"x24" Rectified  
**AL28** 13"x13" Rectified  
**AL25** 20"x20" Rectified



**Limestone AN**  
**AL2W** 13"x13" Mosaic



**Limestone BG**  
**AL2X** 13"x13" Mosaic



**Limestone BI**  
**AL2V** 13"x13" Mosaic



**Limestone MC**  
**AL33** 13"x13" Mix Mosaic



**Limestone AN**  
**AL2Z** 12"x24" Strip Mosaic



**Limestone BG**  
**AL32** 12"x24" Strip Mosaic




**Limestone BI**  
**AL2Y** 12"x24" Strip Mosaic

**Grecian Metallic Deco**  
**AL36** 2"x13"

**TRIMS**



**AL2J** Limestone AN Bullnose  
**AL2K** Limestone BG Bullnose  
**AL2H** Limestone BI Bullnose  
 3"x13"



**AL2M** Limestone AN Cove Base  
**AL2N** Limestone BG Cove Base  
**AL2L** Limestone BI Cove Base  
 6"x12"



**AL2Q** Limestone AN Cove Base In Angle  
**AL2R** Limestone BG Cove Base In Angle  
**AL2P** Limestone BI Cove Base In Angle  
 1"x6"



**AL2T** Limestone AN Cove Base Out Angle  
**AL2U** Limestone BG Cove Base Out Angle  
**AL2S** Limestone BI Cove Base Out Angle  
 1"x6"

- Floor Tile
- Wall Tile
- Modular Tile
- 3d Printing Technique
- Rectified Tile
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- Moderate Variation
- Frost Resistant
- Meets ADA Recommendations
- Abrasion Resistance
- C.O.F. (Wet)
- C.O.F. (Dry)
- Certified No VOC
- 21% Minimum Pre-Consumer Recycled Content



Contributes to LEED Credits

## TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS SCALE
Breaking Strength	12"x24"	≥ 250 lbf.	≥ 806 lbf. C648
	20"x20"	≥ 250 lbf.	≥ 700 lbf. C648
	13"x13"	≥ 250 lbf.	≥ 535 lbf. C648
Facial Dimension	-3.0 % < Nominal ≤ 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.25 % or +/- 0.8 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.40 % or +/- 1.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

\* Whichever is less

