



live inspired

STATUS

GLAZED PORCELAIN TILE



AF2D Status BG
18"x18"



AF2A Status BG
12"x12"



AF2E Status MT
18"x18"



AF2B Status MT
12"x12"



AF2F Status NO
18"x18"



AF2C Status NO
12"x12"

-  Floor Tile
-  Wall Tile
-  Trim Available
-  Suitable for Outdoors
-  **V3** Moderate Variation
-  Frost Resistant
-  Meets ADA Recommendations
-  **IV** Abrasion Resistance
-  **06** C.O.F. (Wet)
-  **06** C.O.F. (Dry)
-  7% Minimum Pre-Consumer Recycled Content
-  **VOc** Certified No VOC

TRIMS



- AF4L** Status BG Bullnose
- AF4M** Status MT Bullnose
- AF4N** Status NO Bullnose
- 3"x12"



Contributes to LEED Credits

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD	
Water Absorption	≤ 0.50%	≤ 0.50%	C373	
Frost Resistance	As Reported	Resistant	C1026	
Scratch Resistance	MOHS 1-10	7	MOHS SCALE	
Breaking Strength	18"x18"	≥ 250 lbf.	≥ 467 lbf.	C648
	12"x12"	≥ 250 lbf.	≥ 364 lbf.	C648
Facial Dimension	-3.0 % < Nominal ≤ 3.0 %	Within Standard	C499	
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499	
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502	
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485	
Abrasion Resistance	Class 0 - Class V	Class IV	C1027	
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028	
C.O.F. (Dry)	As Reported	0.60 ≤ COF < 0.70	C1028	
Chemical Resistance	Class A - Class E	Class A	C650	
Stain Resistance	Class A - Class E	Class A	C1378	

* Whichever is less

