



live inspired

TEXTILE

GLAZED PORCELAIN TILE | RECTIFIED



R8M4 Textile SA
24"x24" Rectified
R8M9 Textile SA
12"x24" Rectified
R8L9 Textile SA
12"x48"* Rectified




R8M5 Textile GR
24"x24" Rectified
R8N0 Textile GR
12"x24" Rectified
R8M0 Textile GR
12"x48"* Rectified




R8M1 Textile MA
24"x24" Rectified
R8M6 Textile MA
12"x24" Rectified
R8L6 Textile MA
12"x48"* Rectified




R8M2 Textile AN
24"x24" Rectified
R8M7 Textile AN
12"x24" Rectified
R8L7 Textile AN
12"x48"* Rectified




AJ2H Textile SA
Mosaic 1"x 3"
12"x12"



AJ2F Textile GR
Mosaic 1"x 3"
12"x12"



AJ2G Textile MA
Mosaic 1"x 3"
12"x12"



AJ2E Textile AN
Mosaic 1"x 3"
12"x12"



R9C0 Damasko SA Rectified
Deco
12"x24"



R9A9 Damasko GR Rectified
Deco
12"x24"



R9A7 Lamè MA
Deco
12"x24" Rectified




R9A6 Lamè NE
Deco
12"x24" Rectified




R8L4 Textile Ramage MA
24"x24"* Rectified



R8L5 Textile Ramage AN
24"x24"* Rectified



R9A5 Lamè MA
Listelli
1 1/8"x24" Rectified




R9A4 Lamè NE
Listelli
1 1/8"x24" Rectified



TRIMS

R8R2 Textile SA Bullnose
R8R3 Textile GR Bullnose
R8Q9 Textile MA Bullnose
R8R0 Textile AN Bullnose
4"x24"



R8Z9 Rattan MA
Deco
12"x24" Rectified



R8Z8 Rattan NE
Deco
12"x24" Rectified

***SPECIAL ORDER**

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS SCALE
Breaking Strength	12"x24" ≥ 250 lbf.	≥ 928 lbf.	C648
Facial Dimension	-3.0 % < Nominal ≤ 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.25 % or +/- 0.8 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.40 % or +/- 1.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class V	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.80 ≤ COF < 0.90	C1028
Chemical Resistance	Class A - Class E	Class B	C650
Stain Resistance	Class A - Class E	Class B	C1378

* Whichever is less

- Floor Tile
- Wall Tile
- Modular Tile
- Rectified Tile
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- Uniform Variation
- Frost Resistant
- Meets ADA Recommendations
- Abrasion Resistance
- C.O.F. (Wet)
- C.O.F. (Dry)
- 44% Minimum Pre-Consumer Recycled Content
- Certified No VOC



Contributes to LEED Credits

