

live inspired



WESTERN STONE

GLAZED PORCELAIN TILE



A392 Canyon City BG
20"x20"
A397 Canyon City BG
13"x13"
A402 Canyon City BG
6 1/2"x6 1/2"



A393 Yukon Trail NO
20"x20"
A398 Yukon Trail NO
13"x13"
A403 Yukon Trail NO
6 1/2"x6 1/2"



A394 Gold Rush GI
20"x20"
A399 Gold Rush GI
13"x13"
A404 Gold Rush GI
6 1/2"x6 1/2"



AF25 Klondike RS
20"x20"
AF2R Klondike RS
13"x13"
AF2Q Klondike RS
6 1/2"x6 1/2"



AE3K Canyon City BG
Mosaic - Square 2"x2"
13"x13"



AE3N Yukon Trail NO
Mosaic - Square 2"x2"
13"x13"



AE3M Gold Rush GI
Mosaic - Square 2"x2"
13"x13"



AF2U Klondike RS
Mosaic - Square 2"x2"
13"x13"

TRIMS



AE33 Canyon City BG Bullnose
AE34 Yukon Trail NO Bullnose
AE35 Gold Rush GI Bullnose
AF2T Klondike RS Bullnose
3"x13"



AH35 Canyon City BG Cove Base
AH36 Yukon Trail NO Cove Base
AH37 Gold Rush GI Cove Base
AH38 Klondike RS Cove Base
6"x8"



AH39 Canyon City BG Cove Base In Angle
AH4A Yukon Trail NO Cove Base In Angle
AH4B Gold Rush GI Cove Base In Angle
AH4C Klondike RS Cove Base In Angle
1"x6"



AH4D Canyon City BG Cove Base Out Angle
AH4E Yukon Trail NO Cove Base Out Angle
AH4F Gold Rush GI Cove Base Out Angle
AH4G Klondike RS Cove Base Out Angle
1"x6"



AF4C Canyon City BG V-Cap
AF4F Yukon Trail NO V-Cap
AF4D Gold Rush GI V-Cap
AF4E Klondike RS V-Cap
2 1/4"x6 1/2"



AF4G Canyon City BG V-Cap Corner
AF4K Yukon Trail NO V-Cap Corner
AF4H Gold Rush GI V-Cap Corner
AF4J Klondike RS V-Cap Corner
3/4"x2 1/4"

- Floor Tile
- Wall Tile
- Modular Tile
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- Substantial Variation
- Frost Resistant
- Meets ADA Recommendations
- Abrasion Resistance
- C.O.F. (Wet)
- C.O.F. (Dry)
- 21% Minimum Pre-Consumer Recycled Content
- Certified No VOC



Contributes to LEED Credits

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	8	MOHS SCALE
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 640 lbf.
	13"x13"	≥ 250 lbf.	≥ 540 lbf.
Facial Dimension	-3.0 % < Nominal ≤ 3.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Whichever is less

