

RAGNO  USA

**WESTERN STONE** GLAZED PORCELAIN TILE | MADE IN THE USA



*live inspired*



live inspired



# WESTERN STONE

GLAZED PORCELAIN TILE | MADE IN THE USA



**A392** Canyon City BG  
20"x20"  
**A397** Canyon City BG  
13"x13"  
**A402** Canyon City BG  
6 1/2"x6 1/2"



**A393** Yukon Trail NO  
20"x20"  
**A398** Yukon Trail NO  
13"x13"  
**A403** Yukon Trail NO  
6 1/2"x6 1/2"



**A394** Gold Rush GI  
20"x20"  
**A399** Gold Rush GI  
13"x13"  
**A404** Gold Rush GI  
6 1/2"x6 1/2"



**AF25** Klondike RS  
20"x20"  
**AF2R** Klondike RS  
13"x13"  
**AF2Q** Klondike RS  
6 1/2"x6 1/2"



**AE3K** Canyon City BG  
Mosaic - Square 2"x2"  
13"x13"



**AE3N** Yukon Trail NO  
Mosaic - Square 2"x2"  
13"x13"



**AE3M** Gold Rush GI  
Mosaic - Square 2"x2"  
13"x13"



**AF2U** Klondike RS  
Mosaic - Square 2"x2"  
13"x13"

TRIMS



**AE33** Canyon City BG Bullnose  
**AE34** Yukon Trail NO Bullnose  
**AE35** Gold Rush GI Bullnose  
**AF2T** Klondike RS Bullnose  
3"x13"



**AH35** Canyon City BG Cove Base  
**AH36** Yukon Trail NO Cove Base  
**AH37** Gold Rush GI Cove Base  
**AH38** Klondike RS Cove Base  
6"x8"



**AH39** Canyon City BG Cove Base In Angle  
**AH4A** Yukon Trail NO Cove Base In Angle  
**AH4B** Gold Rush GI Cove Base In Angle  
**AH4C** Klondike RS Cove Base In Angle  
1"x6"



**AH4D** Canyon City BG Cove Base Out Angle  
**AH4E** Yukon Trail NO Cove Base Out Angle  
**AH4F** Gold Rush GI Cove Base Out Angle  
**AH4G** Klondike RS Cove Base Out Angle  
1"x6"



**AF4C** Canyon City BG V-Cap  
**AF4F** Yukon Trail NO V-Cap  
**AF4D** Gold Rush GI V-Cap  
**AF4E** Klondike RS V-Cap  
2 1/4"x6 1/2"



**AF4G** Canyon City BG V-Cap Corner  
**AF4K** Yukon Trail NO V-Cap Corner  
**AF4H** Gold Rush GI V-Cap Corner  
**AF4J** Klondike RS V-Cap Corner  
3/4"x2 1/4"

- Floor Tile
- Wall Tile
- Modular Tile
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- Substantial Variation
- Frost Resistant
- Meets ADA Recommendations
- Abrasion Resistance
- C.O.F. (Wet)
- C.O.F. (Dry)
- 21% Minimum Pre-Consumer Recycled Content
- Certified No VOC



Contributes to LEED Credits

## TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD	
Water Absorption	≤ 0.50%	≤ 0.50%	C373	
Frost Resistance	As Reported	Resistant	C1026	
Scratch Resistance	MOHS 1-10	7	MOHS SCALE	
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 640 lbf.	C648
	13"x13"	≥ 250 lbf.	≥ 540 lbf.	C648
Facial Dimension	-3.0 % < Nominal ≤ 3.0 %	Within Standard	C499	
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499	
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502	
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485	
Abrasion Resistance	Class 0 - Class V	Class IV	C1027	
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028	
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028	
Chemical Resistance	Class A - Class E	Class A	C650	
Stain Resistance	Class A - Class E	Class A	C1378	

\* Whichever is less

