

STONE EFFECT

Stoneway_Ardesia
Collection






R5JT Stoneway_Ardesia Antracite Str 20x20cm - R5JX Stoneway_Ardesia Antracite Str 20x40cm

Stoneway_Ardesia


With 4 colours and 2 finishes, natural and structured, the Stoneway Ardesia collection is ideal for interpreting indoor and outdoor locations with a fresh, natural style. 5 sizes extend the compositional potential for even greater surface variability. The structured version, also 20 mm thick, allows unusual, creative design solutions to be used even outdoors.

Porcelain Stoneware



Antracite

Size	Superficie	Code	Description	Thikness	Rett.	Caratteristiche tecniche	Use	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Premium Tech.	Scatole	Mq	Kg	Pallet	Mq	Kg
20x20cm	Structured Surface	R5JT	Stoneway_ardesia Antracite Str	MM 09				R11C	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V3		26	1,04	17,74	54	56,16	957,71
20x40cm	Structured Surface	R5JX	Stoneway_ardesia Antracite Str	MM 09				R11C	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V3		13	1,04	18,49	54	56,16	998,40



Beige


Size	Superficie	Code	Description	Thikness	Rett.	Caratteristiche tecniche	Use	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Premium Tech.	Scatole	Mq	Kg	Pallet	Mq	Kg
20x20cm	Structured Surface	R5JS	Stoneway_ardesia Beige Str	MM 09				R11C	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V3		26	1,04	18,44	54	56,16	995,92
20x40cm	Structured Surface	R5JW	Stoneway_ardesia Beige Str	MM 09				R11C	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V3		13	1,04	18,77	54	56,16	1.013,54



Bianco

Size	Superficie	Code	Description	Thikness	Rett.	Caratteristiche tecniche	Use	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Premium Tech.	Scatole	Mq	Kg	Pallet	Mq	Kg
20x20cm	Structured Surface	R5JQ	Stoneway_ardesia Bianco Str	MM 09				R11C	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V3		26	1,04	18,15	54	56,16	980,10
20x40cm	Structured Surface	R5JU	Stoneway_ardesia Bianco Str	MM 09				R11C	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V3		13	1,04	18,54	54	56,16	1.000,89



Porcelain Stoneware



Grigio

Size	Superficie	Code	Description	Thikness	Rett.	Caratteristiche tecniche	Use	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Premium Tech.	Scatole	Mq	Kg	Pallet	Mq	Kg
20x20cm	Structured Surface	R5JR	Stoneway_ardesia Grigio Str	MM 09				R11C	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V3		26	1,04	18,18	54	56,16	981,65
20x40cm	Structured Surface	R5JV	Stoneway_ardesia Grigio Str	MM 09				R11C	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V3		13	1,04	18,38	54	56,16	992,75

Caratteristiche Tecniche

-  Frost proof
-  Resistance deep abrasion

Destinazioni d'uso

D
 Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

E
 Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

F
 Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

Variazioni cromatiche

V0
 Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

V1
 Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

V2
 Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run

G
 Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

H
 Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

V3
 Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

V4
 Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni

							
ISO 14001	ISO 9001	Green Building Council	GPP	EPD Italy	ISO 17889-1	Greenguard	LEED Credits
							
FDES	Declare	HPD	CAM Sassuolo	CE 001MRZI	UKCA 00 1MRZUK		

LEGENDA

CERTIFICAZIONI



© Copyright by Ragno – Marazzi Group S.r.l. 2024. All Rights Reserved Marazzi Group Srl a Socio Unico Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644
info@ragno.it
www.ragno.it

The Company reserves the right, at any time and without prior notice, to change the information and technical characteristics given in this catalogue, none of which are to be considered legally binding. Weights, colours and dimensions are subject to the normal variations resulting from the ceramic firing process. Within the limits of printed material, the colours and aesthetic features of the products illustrated correspond as closely as possible to those of the actual products.

PDF GENERATED AUTOMATICALLY ON 11/05/2026

RAGNO 